

Audio-Technica VMx-serie, stereomodeller - sammenligning



	AT-VM510xCB	AT-VM520xEB	AT-VM530xEN	AT-VM740xML	AT-VM745xML	AT-VM750xSH	AT-VM760xSL
Frekvensområde	20 til 20.000Hz	20 til 20.000Hz	20 til 25.000Hz	20 til 25.000Hz	20 til 27.000Hz	20 til 27.000Hz	20 til 30.000Hz
Kanalseparation	24dB (1kHz)	24dB (1kHz)	25dB (1 kHz)	25dB (1 kHz)	26dB (1 kHz)	26dB (1 kHz)	26dB (1 kHz)
Vertikal sporingsvinkel	20°	20°	20°	20°	20°	20°	20°
Nåletryk	1,8 til 2,2 gram	1,8 til 2,2 gram	1,8 til 2,2 gram	1,8 til 2,2 gram	1,8 til 2,2 gram	1,8 til 2,2 gram	1,8 til 2,2 gram
Nåletype	Limet konisk	Limet elliptisk	Nøgen elliptisk	Nøgen Microlinear	Nøgen Microlinear	Nøgen Shibata	Special Line Contact
Anbefalet belastning	47 k Ohm	47 k Ohm	47 k Ohm	47 k Ohm	47 k Ohm	47 k Ohm	47 k Ohm
Spoleimpedans	3,2 k Ohm (1 kHz)	3,2 k Ohm (1 kHz)	3,2 k Ohm (1 kHz)	3,2 k Ohm (1 kHz)	3,2 k Ohm (1 kHz)	3,2 k Ohm (1 kHz)	3,2 k Ohm (1 kHz)
DC modstand	750 Ohm	750 Ohm	750 Ohm	750 Ohm	750 Ohm	750 Ohm	750 Ohm
Spoleinduktans	480 mH (1 kHz)	480 mH (1 kHz)	480 mH (1 kHz)	480 mH (1 kHz)	480 mH (1 kHz)	480 mH (1 kHz)	480 mH (1 kHz)
Udgangsspænding	5mV (1kHz, 5 cm/sek.)	5mV (1kHz, 5 cm/sek.)	3,2mV (1kHz, 5 cm/sek.)	3,2mV (1kHz, 5 cm/sek.)	3,7mV (1kHz, 5 cm/sek.)	3,7mV (1kHz, 5 cm/sek.)	3,7mV (1kHz, 5 cm/sek.)
Udgangsbalance	1,5dB	1,5dB	1,5dB	1,0dB	1,0dB	1,0dB	1,0dB
Nålefone	Aluminiumsrør	Aluminiumsrør	Aluminiumsrør	Aluminium, tilspidset	Bor, massiv	Bor, massiv	Bor, massiv
Statisk compliance	23 x 10-6 cm/dyne	23 x 10-6 cm/dyne	23 x 10-6 cm/dyne	20 x 10-6 cm/dyne	20 x 10-6 cm/dyne	20 x 10-6 cm/dyne	17,5 x 10-6 cm/dyne
Dynamisk compliance	7 x 10-6 cm/dyne	7 x 10-6 cm/dyne	7 x 10-6 cm/dyne	7 x 10-6 cm/dyne	7 x 10-6 cm/dyne	7 x 10-6 cm/dyne	7 x 10-6 cm/dyne
Anbefalet belastningskap.	150 - 250 pF	150 - 250 pF	150 - 250 pF	150 - 250 pF	150 - 250 pF	150 - 250 pF	150 - 250 pF
Vægt	7,2 gram	7,2 gram	7,2 gram	8,8 gram	8,8 gram	8,8 gram	8,8 gram
Vejl. pris	949,-	1.029,-	1.745,-	2.140,-	2.695,-	3.015,-	5.000,-